Bucket Labeller



Automatic Labelling System for large capacity containers

Designed for your application.



Why the Bucket Labeller?

- Built with an industrial environment in mind with easy wipe stainless steel surfaces.
- Easy to adjust label position due to the directly accessible spindles.
- > Almost silent performance due to quiet processors.
- > Can run in either a right to left or left to right position.
- > Add extras including a thermal inkjet or thermal transfer printer for direct marking or label printing.
- Adjustable conveyor speeds to suit your product.
- Up to 15 ppm depending on product and label length.
- > Up to 25 stored programmable memory files for quick and accurate changeovers.

Bucket Labeller



Automatic Labelling System for conical containers

Technical Specification

Label head	120, 200, 250 or 300mm web widths, left or right handed. Roll max 270mm diameter, 45mm or 76mm ID cores.
Conveyor	Width and length of system to fit your requirements.
Thermal Inkjet Printer (Optional)	Print area 1-50mm x 150mm.
Thermal Transfer Printer (Optional)	Print area up to 162mm wide. Label design software & consumables.
Drive	Stepper, multi-phase or mircrostep. Servo
Services	230v AC 50/60Hz

Options

Upgrade to heavy duty servo head
Operator keypad and display
Digital turn wheel to all positioning adjustments
Thermal inkjet, Thermal transfer or Continuous inkjet printers
Sensors for clear and non-transparent labels
Variable speed controlled conveyor
PCL with HMI Control

You produce it, We label it.